



CAM 0159-TVI (Hybrid)

T. Sales

+44 (0)115 714 9990

+44 (0)1623 541 411

Technical

+44 (0)115 714 9999

+44 (0)1623 549 999

E. sales@vdomain.co.uk

W. www.vdomain.co.uk
www.webeyecms.com

Vandal Resistant Dome Camera

- 2.8-11mm VF
- Sony CMOS
- 1000 TVL (analogue)
- 2.43 MP (HD TVi)
- WDR and D-WDR
- DNR, Privacy and de-fog functions



SECURITY
SAFETY
TECHNOLOGY
INNOVATION

24:C SPECIFICATION SHEET

cameras

CAM 0159-TVI (Hybrid)

Vandal Resistant Dome Camera

Image Sensor	1/3 2.43MEGA CMOS	White Balance	AUTO/AUTO EXT/PUSH/Manual
DSP	Sony	Sens Up	x 2 x 4 x 8 x 16 x 32
Scanning System	2:1 Interlace	3D DNR	20 + 3DNR OFF / LOW / MIDDLE / HIGH
Video Format	PAL/NTSC	BLC	On/Off (Level Setting)
CCD Total Pixels	PAL: 752x582	Gain Control	AGC - Low/High/Off Selectable
Resolution	1/3 TVI : 2.43Megapixel / Analog : 1,000TVL	Mirror	On/Off
Sync System	Internal	Day/Night	Colour/BW/Auto/Ext
S/N Ratio	50dB (AGC Off / Weight On)	Privacy	16 Areas (ON, OFF, COLOUR, POSITION)
Min. Illumination (F 1.2)	Color : 0.1 Lux(50IRE) / 0.02 Lux(15IRE)	IP Rating	IP65
	B/W : 0.08 Lux(50IRE) / 0.002 Lux(15IRE)	Working Temperature	Absolute: -10°C ~ +50°C
Lens	2.8mm - 11mm Vari-Focal	Power Consumption	DC 12V +- 10% AC24V +- 10% < 1.8 Watts
Video Output	1TVI 1.0 Vp-p (75 Ohms, terminated)	Power Supply	12V DC
Shutter Speed	PAL 1/30 (1/25) ~ 1/30K Sec	Dimensions	111H x 136 D mm

T. Sales

+44 (0)115 714 9990

+44 (0)1623 541 411

Technical

+44 (0)115 714 9999

+44 (0)1623 549 999

E. sales@vdomain.co.uk

W. www.vdomain.co.uk
www.webeyecms.com

