



DATASHEET XANTCABL

Auteurs : Frédéric LANCELIN
Diffusion : RSI Video Technologies
Date : 07/02/2011
Ref : Datasheet XANTKIT-EU.doc
Version : 1.0 – FR

Suivi des versions :

Date	Version	Auteur	Modifications
07/02/2011	0.1	F. LANCELIN	Creation
07/02/2011	1.0	F. LANCELIN	Release

1. Introduction

The XANTCABL consists of 1 (one) cable that allow you to plug an external antenna to a XV200 or XT200.


NOTE : The externals antennas are **NOT** provided with this cable.

A kit to extend the RSI radio range is available under another reference XANTKIT-EU.

2. Kits

The cable is a MMCX to SMA connector that plugs directly into the MMCX connectors of the XT200 or XV200.

This cable can be used to extend either the RSI radio range or the GPRS range.




3. Programming and Cabling


a. RSI Radio range

The MMCX to SMA cable allows only the connection of a 3rd party provider Radio antenna.

NOTE : The RADIO antenna is **NOT** provided with this cable.



The external RSI radio antenna must be enabled under Configuration // General Parameters accessible at level 4 only.



b. GPRS range

To extend the GPRS range, just unplug with great caution the existing GPRS antenna and plug the MMCX-to-SMA cable.

The MMCX-to-SMA cable allows only the connection of a 3rd party provider GPRS antenna.



NOTE : The GPRS antenna is **NOT** provided with this cable.

NOTE : Proceed with great care and caution when unplugging the existing GPRS antenna.