

### Applications

- > Programming and operating Videofied security systems.

### Electrical Data

Intercom number per panel	3 max
Power supply	Powered by the panel
Tamper	Mechanically possible
Operation	Half duplex
<b>Loudspeaker</b>	
Output power	0.75 W max Adjustable and accessible in front cover
Audio level	87 dBA
Impedance	16 $\Omega$
<b>Microphone</b>	
Type	Electret omni directional
Sensitivity	Fixed, 42dB
Shocks	IK07
Protection	IP30
Operating temperature	0°/+40°C (32°/104°F)
Maximum relative humidity	70%, non-condensing
Approvals	CE

### Physical Data

Material	ABS-ULV0
Dimensions	110 mm x 79 mm x 35 mm
Weight	120 g

TP means TP100 for France.

### Installation/Mounting

Connector type	By screwed contacts
Contacts number	8
Wiring type	Daisy chain or direct to the panel
Wire	By cutting 2 lugs at the back/top cover depending on case
Cable type Gauge	AWG24
Wall fixing	2 screws
Positioning	By oblong holes
Front cover closing	By bottom screws

### Connector Pinout

Name	Nb
AP	1
VCC	2
GND	3
MIC	4
HP	5
CMD	6
VS-	7
VS+	8

